

Roll-In Freezer

| Model | Swing Doors | Cu. Ft. | HP | Amps | Crated Weight | Cabinet Dimensions | | |
|---|-------------|---------|-----|------|---------------|--------------------|----------|--------|
| | | | | | | L | D | H* |
| <i>SOLID DOORS</i> | | | | | | | | |
| TG1FRI-1S | 1 | 37 | 3/4 | 12.2 | 485 | 35 x | 34 1/2 x | 83 3/4 |
| <small>All dimensions rounded up to the nearest 1/8".</small> | | | | | | | | |

* Height does not include 1" for system mechanical components.



TG1FRI-1S

FEATURES/BENEFITS

- Oversized and balanced, **environmentally friendly (R404A), refrigeration system**, factory sealed and pre-lubricated for long life.
- **Freezer holds -10°F** (air off evaporator coil, -20°F) for the best in food preservation.
- An ideal -10°F for roll-in racks supporting frozen food and ice cream.
- Accepts roll-in rack (inboard castor) with maximum dimensions of 27"W x 29"D x 66"H. (supplied by others).
- **300 series stainless steel doors and front** (the finest stainless available).
- Anodized quality aluminum sides, bottom and back.
- Interior - attractive, **NSF approved**, white aluminum sides and back. **300 series stainless floor and door liner.**
- **Lifetime guaranteed recessed door handles.**
- Three rugged **cam-lift hinges** per door-lifetime guaranteed. Designed for easy product access with a full 180 degree open capability and stay open feature at 120 degrees.
- **Heavy gauge stainless steel ramp standard.**
- Door locks standard.
- Exterior mounted **digital electronic thermometer** features manual defogger.
- Incandescent interior lighting.
- **Interior bumpers protect cabinet.**
- Foamed-in-place polyurethane **high density cell insulation** (CFC Free).
- Automatic defrost system time-initiated, temperature-terminated.
- Automatic evaporator fan motor delay during defrost cycle.
- Minimum wattage heater in cabinet frame.
- **Energy saver switch.**
- **Standard backguard** improves airflow.
- Field reversible door swing.
- Self-contained system.
- Reversible wiper gaskets for positive seal.

Remote cabinets available 14% off list (condensing units supplied by others; system comes standard with 404A expansion valve and requires R404A refrigerant). Consult factory technical service dept. for BTU information.