

Roll-In Refrigerators

Model	Swing Doors	Cu. Ft.	HP	Amps	Crated Weight	Cabinet Dimensions		
						L	D	H*
SOLID DOORS								
TG1RRI-1S	1	37	1/3	8.9	400	35	34 1/2	83 3/4
TG2RRI-2S	2	75	1/2	11.8	706	68	34 1/2	83 3/4
SOLID DOORS 89" HIGH								
TG1RRI89-1S	1	38	1/3	8.9	485	35	34 1/2	89
TG2RRI89-2S	2	80	1/2	11.8	786	68	34 1/2	89

All dimensions rounded up to the nearest 1/8".

* Height does not include 1" for system mechanical components.

The new consultant choice for roll-in rack applications.



TG1RRI89-1S



TG2RRI89-2S



TG1RRI-1S

FEATURES/BENEFITS

- Oversized and balanced, **environmentally friendly, refrigeration system**, factory sealed and pre-lubricated for long life.
- Food safe refrigerators **hold 33°F to 38°F**.
- Accepts roll-in rack (inboard castor) with maximum dimensions of 27"W x 29"D x 66"H. TG1RRI89-1S and TG2RRI89-2S accept roll-in rack (inboard castor) with maximum dimensions of 27"W x 29"D x 72"H. (supplied by others)
- **300 series stainless steel doors and front** (the finest stainless available).
- Anodized quality aluminum sides, bottom and back.
- Interior - attractive, **NSF approved**, white aluminum sides and back. **300 series stainless floor and door liner**.
- **Heavy gauge doors**.
- Three rugged **cam-lift hinges** per door-lifetime guaranteed. Designed for easy product access with a full 180 degree open capability and stay open feature at 120 degrees.
- **Heavy gauge stainless steel ramp** standard for each door.
- Exterior mounted digital electronic thermometer features manual defogger.
- **Interior bumpers protect cabinet**.
- Foamed-in-place polyurethane **high density cell insulation** (CFC Free).
- Incandescent interior lighting.
- **Energy saver switch**.
- **Lifetime guaranteed recessed door handles**.
- Door locks standard.
- Top mounted unit positioned out of food zone to maximize storage capacity.
- Glass condensate pan to prevent electrolysis.
- Hot gas condensate for energy efficiency.
- Self-contained system.
- Reversible wiper gaskets for positive seal.
- **Field reversible door swing**.

Remote cabinets available 14% off list (condensing units supplied by others; system comes standard with 404A expansion valve and requires R404A refrigerant). Consult factory technical service dept. for BTU information.